

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/008269 A1

(51) International Patent Classification⁷: **G01R 33/561**,
33/3415, G06F 15/80

(74) Common Representative: **KONINKLIJKE PHILIPS
ELECTRONICS N.V.**; c/o LUNDIN, Thomas, M., 595
Miner Road, Cleveland, OH 44143 (US).

(21) International Application Number:

PCT/IB2004/002331

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(22) International Filing Date: 16 July 2004 (16.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/489,429 23 July 2003 (23.07.2003) US

(71) Applicant (for all designated States except US): **KONIN-
KLJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for AE only): **U.S. PHILIPS CORPORA-
TION** [US/US]; 1251 Avenue of the Americas, New York,
NY 10510-8001 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **GRAESSLIN,**
Ingmar [DE/NL]; P.O. Box 220, NL-5600 AE Eind-
hoven (NL). **EGGERS, Holger** [DE/NL]; P.O. Box 220,
NL-5600 AE Eindhoven (NL).

Published:

— with international search report

[Continued on next page]

(54) Title: EFFICIENT MAPPING OF RECONSTRUCTION ALGORITHMS FOR MAGNETIC RESONANCE IMAGING
ONTO A RECONFIGURABLE RECONSTRUCTION SYSTEM



(57) Abstract: A magnetic resonance (MR) system (10) includes radiofrequency (RF) transmitters (34) which send RF pulses into an examination region (14) to excite a spin system to be imaged. Coil elements (20, 24, 28) pick up an MR signal, which is demodulated and converted into digital data by RF receivers (36). A plurality of independent parallel processing channels (42₁, 42₂, ..., 42_n) is operatively connected to the RF receivers to reconstruct images from the digital data. The parallel processing channels (42₁, 42₂, ..., 42_n) include one or more pipeline stages (54₁, 54₂, ..., 54_n). Processing channels and pipeline stages include a plurality of processing or reconstruction units (52). Processing tasks are dynamically allocated to these processing or reconstruction units on a per scan basis using a single general strategy for mapping processing tasks to hardware resources. The connections (56) between the processing or reconstruction units (52) are reconfigured using a switching means (60). In this manner, different numbers of coil elements (20, 24, 28) can be connected with matching numbers of processing channels (42₁, 42₂, ..., 42_n) to exploit available processing resources optimally.

WO 2005/008269 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.